

General Corded Scanner



1070

1000

1090+

1100

	1070	1000	1090+	1100	
Performance	Category	CCD contact scanner	CCD contact scanner	CCD contact scanner (for codes up to 90mm wide)	Linear imaging scanner
	Optical sensor	1500 pixels	2048 pixels		3648 pixels
	Light source	Red LED (623 nm)	Red LED (660 nm)	Red LED (650 nm)	Red LED (630 nm)
	Resolution	4 mil	3 mil	4 mil	3 mil
	Depth of field 13 mil barcode	0 to 3cm / 0 to 1.2 in.	0 to 1cm / 0 to 0.4 in.	0 to 5cm / 0 to 2 in.	2.5 to 20 cm / 1 to 7.9 in.
	Scanning angle	Pitch $\pm 70^\circ$ Skew $\pm 40^\circ$		Pitch $\pm 70^\circ$ Skew $\pm 70^\circ$	
	PCS	Minimum 45%	Minimum 30%		
	Scan rate	100 scans / second			
	Auto-sense mode	n / a			Yes
	Interfaces supported	Keyboard wedge, USB	RS232, Keyboard wedge, Wand emulation (except 1000), USB HID, USB Virtual Com, IBM 4683/4694		
	Barcodes supported	Codabar, Code 39, Code 93, Code 128, GS1 DataBar (RSS), Industrial 2 of 5, Interleave 2 of 5, Matrix 2 of 5, MSI, Italian and French Pharmacodes, Plessey, Telepen, UPC / EAN / GS1-128, and more			
	Programmable features	Data editing, interface selection, symbology configuration			
	Language support	US and UK English, French, Italian, Belgian, Norwegian, Swedish, Spanish, Portuguese, German			
Physical	Dimension L x W x H	16.7 x 7.5 x 5.7 cm / 6.6 x 3 x 2.2 in.	17 x 8 x 4.8 cm / 6.7 x 3.1 x 1.9 in.	18.2 x 10.4 x 6.4 cm / 7.2 x 4.1 x 2.5 in.	14.5 x 9.3 x 7.4 cm / 5.7 x 3.7 x 2.9 in.
	Weight without cable	104 g / 3.7 oz.	265 g / 9.3 oz. (w/cable)	148 g / 5.2 oz.	165 g / 5.8 oz.
	Color	Black	Ivory or Black	Ivory	Light gray or dark gray
	Switch	Rubber switch			Micro switch
Electrical	Voltage	+5V $\pm 5\%$			+5V $\pm 10\%$
	Power consumption Standby / Operating	35 mA / 180 mA	40 mA / 95 mA	45 mA / 105 mA	60 mA / 190 mA
User Environment	Operating temperature	0 ° to 50°C / 32° to 122°F			
	Storage temperature	-20° to 60°C / -4° to 140°F			
	Operating/storage humidity Non-condensing	10% to 90% / 0% to 95%	10% to 90% / 5% to 95%		
	Impact resistance Multiple drops onto concrete	1.2 m / 4 ft. Drops	1.0 m / 3.3 ft. Drops		2m / 6.6 ft. Drops
	Electrostatic discharge	Conforms to ± 15 kV air discharge and ± 8 kV contact discharge			
	EMC regulation	BSMI, CE, C-Tick, FCC, IC, KC	BSMI, CE, C-Tick, FCC, IC, KC		BSMI, CE, C-Tick, FCC, IC
Configuration	Setup options include Windows®-based ScanMaster/ScanManager, by direct connection or printing out barcode settings				
Accessories	includes attached cable			Detachable cable, desk / wall mount included with 1100 Optional auto-sense stand for 1100	
Warranty	3 years		5 years		

ACCESSORIES

Auto-sense Stand



1100/1105 Holder
Can be used on tabletop
or wall mounted



CIPHER LAB
Smarter

HEADQUARTERS
CipherLab Co., Ltd.
12F, 333 Dunhua S. Rd., Sec.2
Taipei, Taiwan 10669
Tel +886 2 8647 1166
Fax +886 2 8732 3300
www.cipherlab.com

CipherLab Electronics Trading
J Room, 4F, No.728 West Yan'an
Road, Changning District, Shanghai
China 200050
Tel +86 21 3368 0288
Fax +86 21 3368 0286

CipherLab USA Inc.
2552 Summit Avenue
Plano, Texas USA 75074
Tel +1 469 241 9779
Toll Free 888 300 9779
Fax +1 469 241 0697

CipherLab GmbH
Gießerallee 21
47877 Willich
Germany
Tel +49 2154 89777 20
Fax +49 2154 89777 32